



TRANSMISSION INSTALLATION CHECKLIST

!!!! STOP !!!!

This transmission may be shipped without a filter! You **MUST** replace the filter before installation. This transmission may be electronic, or throttle pressure controlled. The cable/linkage must be properly adjusted after installation. Also You may need to reflash or clear the computer store codes. See manual for adjustment procedures. Failure to correctly set pressure voids your warranty!

An ASE Certified Mechanic must perform the installation.

SAVE ALL RECEIPTS for seals, fluids, etc. Be prepared to provide copies if needed.

Replace transmission filter and pan gasket. Replace **ALL** seals.

Flush and flow test cooler and lines in accordance with the vehicle manufacturer's guidelines. This includes reviewing the manufacturer's latest **TECHNICAL SERVICE BULLETINS**. Replace auxiliary cooler if equipped.

Fully engage converter in front pump

Install as required, with all dowel pins

Check throttle cable/linkage. Make sure they are good!

Fill the transmission and differential/final drive with fluid to the proper levels using the proper types in accordance with the vehicle manufacturer's guidelines.

This includes reviewing the manufacturer's latest **TECHNICAL SERVICE BULLETINS**.

Adjust throttle pressure. Clear stored fault codes.

Install in-line filter if TSB requires it.

Test drive, re-check and adjust as needed

Computer controlled transmissions need to have scan tool attached to check for codes

If transmission malfunctions - **DO NOT DRIVE IT – CALL YOUR REPRESENTATIVE FOR FURTHER INSTRUCTIONS.**

TRANSMISSION WARRANTY

Improper detent adjustment, low fluid level, not using proper fluid, not replacing new filter or improper installation voids all warranties. All conditions under terms of sale apply. Tolpa's Auto Parts recommends the buyer replace front seal, rear seal, pan gasket, filters, and axle shaft seals when applicable prior to installation, as these are not covered by warranty.